

Note:

1.Material

- 1.1: Housing: High Temperature plastic,UL94V-0.
- 1.2: Actuator: High Temperature plastic,UL94V-0.
- 1.3: Contact: Copper Alloy.
- 1.4: Fit: Copper Alloy.

2.Plating

- 2.1: Contact: Tin plated over Nickel on contact area.
Tin plated over Nickel on solder area.
- 2.2: Fit: Tin plated over Nickel.

3.Rating:

- 3.1: Operating Voltage: 30V AC/DC.
- 3.2: Current Rating: 0.4A AC/DC.
- 3.3: Operating Temperature: -40°C~+85°C.

4.Pater Number:

CKT	A	B	C
4	3.00	5.10	9.05
5	4.00	6.10	10.05
6	5.00	7.10	11.05
7	6.00	8.10	12.05
8	7.00	9.10	13.05
9	8.00	10.10	14.05
10	9.00	11.10	15.05
11	10.00	12.10	16.05
12	11.00	13.10	17.05
13	12.00	14.10	18.05
14	13.00	15.10	19.05
15	14.00	16.10	20.05
16	15.00	17.10	21.05
17	16.00	18.10	22.05
18	17.00	19.10	23.05
19	18.00	20.10	24.05
20	19.00	21.10	25.05
21	20.00	22.10	26.05
22	21.00	23.10	27.05
23	22.00	24.10	28.05
24	23.00	25.10	29.05
25	24.00	26.10	30.05
26	25.00	27.10	31.05
27	26.00	28.10	32.05
28	27.00	29.10	33.05
29	28.00	30.10	34.05
30	29.00	31.10	35.05

FDU 10 25 -XX (11 Z)

Plating: Tin

Number of contacts

Series of the product height

Pitch between:10=1.0mm

SUNFUN TECHNOLOGY LTD


DIMENSIONS INIT: mm
UNLESS OTHERWISE SPECIFIABLE

DIMENSION	TOLERANCE
X.X: ±	0.25
X.XX: ±	0.15
X.XXX: ±	0.10
ANGULAR: ±	1°

PRODUCT NAME :
Pitch1.0 FPC CONN- Drawer type w/ 2.5H Top contact

PRODUCT NO. :
FDU1025-XX(11Z)

DRAWING NO. :
FDU1025(A0)



DRAWING: Dain

DATE: 2012/07/03

CHECK: Jack

DATE: 2012/07/03

APPROVED: Jack

DATE:

SCALE: DWG' ID: REV.: PAGE:
C D A1 1/1

REVISION NO.	ECR NO.	DESCRIPTION	MARK	DATE
A		新发行		2012/07/03
1				
2				
3				