

REV.	ECN NO.	LOCATIONS	DESCRIPTION	DATE	DESIGN
N2			UPDATE THE LAYOUT	10/19'26	Sun

ORDERING INFORMATION

MCCFT -Z1K3 (XX T)

1 2 3

1 PRODUCT SERIES:

USB C TYPE connector –
Receptacle (Female) side.

2 ITEM NO.:


Right Angle– Single Row SMD 16pin
Sink1.6 with DIP0.7L/ Body 6.5L

CUSTOMER DRAWING






RoHS Compliant

3 GOLD PLATING :

01: G/F.
03: 3u".
15: 15u".
30: 30u".



3D VIEW



RECOMMENDED P.C.B LAYOUT

TOLERANCE UNSPECIFIED ±0.05mm

NOTES:

1. MATERIAL:

- (1) HOUSING: HIGH TEMP plastic, UL94 V-0.
- (2) CONTACT: COPPER ALLOY.
- (3) MID PLATE: STAINLESS STEEL.
- (4) SHELL: STAINLESS STEEL.

2. PLATED:

- (1) CONTACT: GOLD ON CONTACT AREA OVER NICKEL PLEATED OVER ALL.
- (2) SHELL: NICKEL PLATED OVER ALL.
- (3) MID PLATE: CLEAR ONLY

3. MECHANICAL PERFORMANCE,


- 3-1.INSERTION FORCE: 5~20N.
- 3-2.REMOVAL FORCE: 8~20N.
- 3-3.DURABILITY: 10,000 CYCLES.

4. ELECTRICAL PERFORMANCE,

- 4-1. CURRENT RATING: 5.0A
- 4-2. VOLTAGE RATING: 20V

5. ENVIRONMENTAL PERFORMANCE:

- OPERATING TEMPERATURE: -40°C~+85°C.



PIN ASSIGNMENTS

PIN NO.	A1	A4	A5	A6	A7	A8	A9	A12
SIGNAL NAME	GND	VBUS	CC1	Dp1	Dn1	SBU1	VBUS	GND
PIN NO.	B12	B9	B8	B7	B6	B5	B4	B1
SIGNAL NAME	GND	VBUS	SBU2	Dn2	Dp2	CC2	VBUS	GND

DIM	TOL
X.X	±0.30
X.XX	±0.20
X.XXX	±0.10

SUNFUN		SUNFUN TECHNOLOGY LTD			
DRAW NO.	MCCFT-Z1K3(N2)	DATE	10/19'26	MATERIAL:	SEE NOTES
DESIGN:	Sun	10/19'26	FINISH:	SEE NOTES	
CHECK:	Sun	10/19'26	FILE:	MCCFT-Z1K3(N2)	
REVIEW:	Ziv	10/19'26	P/N:	MCCFT-Z1K3(XXT)	
APPROVED	Ziv	10/19'26	REV. N2	SCALE	
				DRAW NAME:	
				USB C Type CONN – FEMALE	
				Right Angle– Single Row SMD 16pin	
				Sink1.6 with DIP0.7L /Body 6.5L	
				MODEL: USB C TYPE CONN	
				UNIT:	SHEET:
				mm	1/1